

NOTE:


1. CABLE: 28AWG X 25C, AL-FOIL SHIELDED WITH DRAIN WIRE, UL2464,BEIGE(BG-02) PVC JACKET. $\phi 7.0 \pm 0.15$ mm.
2. CONNECTOR: P1:D-SUB 25PIN FEMALE: SOLDER TYPE,BLACK PBT INSULATION,GOLD FLASH CONTACTS,UL RECOGNIZED.WITH HEX NUT.
P2:D-SUB 25PIN MALE:SOLDER TYPE,BLACK PBT INSULATION,GOLD FLASH CONTACTS,UL RECOGNIZE.
3. HEX NUT:#M-2.6.
4. THUMB SCREW TO BE MOLDED BEIGE (BG-02) PVC, UL94V-0.
5. SHIELDING: AL-FOIL TAPE COVER PREMOLD AND 100% CONTACT WITH SHELL.
6. ALL HOOD: MOLDED BEIGE (BG-02) PVC, UL94V-0.
7. TESTING: 100% ELECTRICAL TESTING.

PIN OUT

P1	P2
1	1
2	2
3	3
4	4
5	5
...	...
22	22
23	23
24	24
25	25
SHELL	SHELL (DRAIN)

CHART

P/N	**	xx	L	T
3232-25M25F-03NMUU	03	3	914	+50/-0
3232-25M25F-06NMUU	06	6	1829	+75/-0
3232-25M25F-10NMUU	10	10	3048	+75/-0
3232-25M25F-15NMUU	15	15	4572	+75/-0

NET MECHANISM Corp www.cabling-ol.net				
SCALE	NONE		REV	C
UNIT	MM			
SHEET	1/1	DWG NO.		
DATE	10/25/06			
TITLE DB25F TO DB25M				
PART NO. 3232-25M25F-XXNMUU				