

PIN OUT

P1	P2
1	1
2	2
3	3
4	4
5	5
22	22
23	23
24	24
25	25
SHELL	SHELL (DRAIN)

NOTE:

1. CABLE: 28AWG X 25C, AL-FOIL SHIELDED WITH DRAIN WIRE, UL2464,BEIGE(BG-02) PVC JACKET.ø7.0±0.15mm.
2. CONNECTOR: P1 & P2:D-SUB 25PIN MALE: SOLDER TYPE,BLACK PBT INSULATION,GOLD FLASH CONTACTS,UL RECOGNIZED.
3. THUMB SCREW TO BE MOLDED BEIGE (BG-02) PVC, UL94V-0.
4. SHIELDING: AL-FOIL TAPE COVER PREMOLD AND 100% CONTACT WITH SHELL.
5. ALL HOOD: MOLDED BEIGE (BG-02) PVC, UL94V-0.
6. TESTING: 100% ELECTRICAL TESTING.
7. EACH ONE WITH FOUR #4-40 UNC SCREW.

CHART:

P/N	XX(FT)	L(MM)	TOLERANCE(MM)
3232-25M25M-03	3	914	+50/-0
3232-25M25M-06	6	1829	+75/-0
3232-25M25M-10	10	3048	+75/-0
3232-25M25M-15	15	4572	+75/-0
3232-25M25M-25	25	7620	+150/-0
3232-25M25M-33	33	10058	+150/-0
3232-25M25M-50	50	15240	+300/-0



2PCS/BAG



2PCS/BAG

REV	DESCRIPTION OF CHANGE	DATE
B	ADD 4PCS #4-40 SCREW	05/03/10
A	INITIAL RELEASE	11/01/05

MERCHANDISE MOQ	EACH 50PCS
LEAD TIME	15 DAY
CABLE MOQ	
CONNECTOR MOQ	

NET MECHANISM Corp
www.cabling-ol.net

SCALE	NONE	REV	B
UNIT	MM		
SHEET	1/1	DWG NO.	
DATE	05/03/10		

TITLE: DB25M TO DB25M

PART NO.: 3232-25M25M-XX