

NOTE:


1. CABLE: 28AWG X 25C, AL-FOIL SHIELDED WITH DRAIN WIRE, UL2464,BEIGE(BG-02) PVC JACKET. $\phi 7.0 \pm 0.15$ mm.
2. CONNECTOR: P1 & P2:D-SUB 25PIN MALE: SOLDER TYPE,BLACK PBT INSULATION,GOLD FLASH CONTACTS,UL RECOGNIZED.
3. THUMB SCREW TO BE MOLDED BEIGE (BG-02) PVC, UL94V-0.
4. SHIELDING: AL-FOIL TAPE COVER PREMOLD AND 100% CONTACT WITH SHELL.
5. ALL HOOD: MOLDED BEIGE (BG-02) PVC, UL94V-0.
6. TESTING: 100% ELECTRICAL TESTING.

PIN OUT

P1	—————	P2
1	—————	1
2	—————	2
3	—————	3
4	—————	4
5	—————	5
—	—————	—
—	—————	—
—	—————	—
—	—————	—
—	—————	—
22	—————	22
23	—————	23
24	—————	24
25	—————	25
SHELL	—————	SHELL (DRAIN)

CHART:

P/N	**	xx	L	T
3232-25M25M-03UU	03	3	914	+50/-0
3232-25M25M-06UU	06	6	1829	+75/-0
3232-25M25M-10UU	10	10	3048	+75/-0
3232-25M25M-15UU	15	15	4572	+75/-0

NET MECHANISM Corp www.cabling-ol.net				
SCALE	NONE		REV	B
UNIT	MM			
SHEET	1/1	DWG NO.		
DATE	06/11/05			
TITLE DB25M TO DB25M				
PART NO. 3232-25M25M-XXUU				