



WIRE LIST

P1		P2
1	_____	1
2	_____	2
3	_____	3

REMARK:

- 1.CONSTRUCTION: SHAPE AND DIMENSIONS SUBJECT TO ATTACHED CHARTREGULATION.APPEARNCE:EVERY PART SHOULD BE FINISHED NOT TO DILAPIDTION. CRACK AND BAD FLATING.
- 2.P1:3.5MM STEREO PLUG,GOLD PLATED SHELL,GOLD PLATED CONTACT, AND P2:6.35MM STEREO Jack,GOLD PLATED SHELL,GOLD PLATED CONTACT.
- 3.ADAPTER INSERION EXTRSCTION: FORLE 0.5Kg TO 2.5Kg.
- 4.ELECTRONIC CHARCTERISTICS: CONTACT RESISTANCE:10M Ω
INSULATION RESISTANC: 20M Ω WITHSTAND VOLTAGE AC:150V DC:250V,
CURRENT RATING AC:100V/0.5A DC:150V/1A.
5. OPERATING TEMPERATURE-30°C-+60°C AND ELECTRICAL LITE IS 5000 TIMES INSERTING LEXTRACTING CIT FALL LOAD.
- 6.OVERMOLD COLOR IS BLACK AND MATERIAL PVC PLASTIC.

NET MECHANISM Corp www.cabling-ol.net				
SCALE	NONE		REV	A
UNIT	MM			
SHEET	1/1	DWG NO.		
DATE	03/08/06			
TITLE ø3.5mm STEREO PLUG ø6.3mm STEREO JACK				
PART NO. 35M-63F				