


### WIRE LIST

P1		P2
1	_____	1
2	_____	2
3	_____	3

### REMARK:

- 1.CONSTRUCTION: SHAPE AND DIMENSIONS SUBJECT TO ATTACHED CHARTREGULATION.APPEARANCE:EVERY PART SHOULD BE FINISHED NOT TO DILAPIDTION. CRACK AND BAD FLATING.
- 2.P1:3.5mm STEREO JACK,NICKEL PLATED SHELL AND P2:3.5mm STEREO JACK,NICKEL PLATED SHELL.
- 3.ADAPTER INSERION EXTRSCTION: FORLE 0.5Kg TO 2.0Kg.
- 4.ELECTRONIC CHARCTERISTICS: CONTACT RESISTANCE:20MΩ  
INSULATION RESISTANC: 20MΩ WITHSTAND VOLTAGE AC:150V DC:250V  
CURRENT RATING AC:100V/0.5A DC:200V/0.5A
5. OPERATING TEMPERATURE-30°C-+60°C AND ELECTRICAL LITE IS 5000 TIMES INSERTING LEXTRACTING CIT FALL LOAD.
6. OVERMOLD COLOR IS BLACK AND MATERIAL IS PVC PLASTIC.

NET MECHANISM Corp www.cabling-ol.net				
SCALE	NONE		REV	A
UNIT	MM			
SHEET	1/1	DWG NO.		
DATE	06/17/05			
TITLE	ø3.5mm STEREO JACK TO JACK			
PART NO.	35MF-35MF			