



WIRE LIST

P1		P2
1	_____	1
2	_____	2

REMARK:

- 1.CONSTRUCTION: SHAPE AND DIMENSIONS SUBJECT TO ATTACHED CHARTREGULATION.APPEARANCE:EVERY PART SHOULD BE FINISHED NOT TO DILAPIDTION. CRACK AND BAD FLATING.
- 2.P1:RCA JACK,NICKEL PLATED SHELL,AND P2: 3.5MM MONO PLUG,NICKEL PLATED SHELL.
- 3.ADAPTER INSERION EXTRSCTION: FORLE 0.5KG TO 2.0KG
- 4.ELECTRONIC CHARCTERISTICS: CONTACT RESISTANCE:50M  $\Omega$   
INSULATION RESISTANC: 20M $\Omega$ WITHSTAND VOLTAGE AC:250V DC:300V  
CURRENT RATING AC:100V/0.5A DC:250V/1A
5. OPERATING TEMPERATURE-30°C-----+60°C AND ELECTRICAL LITE IS 5000 TIMES INSERTING LEXTRACTING CIT FALL LOAD.
- 6.NO OVMOLD.

NET MECHANISM Corp www.cabling-ol.net				
SCALE	NONE		REV	A
UNIT	MM			
SHEET	1/1	DWG NO.		
DATE	06/17/05			
TITLE 3.5MM MONO PLUG MALE TO RCA FEMALE				
PART NO. 35MM-RCAF				