



NOTE:

1. CABLE: 28AWG X 9C, AL-FOIL SHIELDED WITH DRAIN WIRE, UL2464,BEIGE (BG-02) PVC JACKET $\phi 5.0 \pm 0.15$ mm.
2. CONNECTOR: P1:D-SUB 9PIN FEMALE:SOLDER TYPE,GOLD FLASH CONTACTS. UL RECOGNIZED.
P2:D-SUB 25PIN MALE:SOLDER TYPE,GOLD FLASH CONTACTS. UL RECOGNIZED.
3. THUMB SCREW TO BE MOLDED BEIGE(BG-02)PVC, UL94V-0.
4. SHIELDING: AL-FOIL TAPE COVER PREMOLD AND 100% CONTACT WITH SHELL.
5. ALL HOOD: MOLDED BEIGE(BG-02) PVC.UL94V-0.
6. TESTING:100% ELECTRICAL TESTING.

PIN OUT

| P1 | P2 |
|----|----|
| 1 | 8 |
| 2 | 3 |
| 3 | 2 |
| 4 | 20 |
| 5 | 7 |
| 6 | 6 |
| 7 | 4 |
| 8 | 5 |
| 9 | 22 |

(DRAIN WIRE)SHELL ——— SHELL

CHART:

| P/N | XX(FT) | L(MM) | TOLERANCE(MM) |
|----------------|--------|-------|---------------|
| 4232-25M09F-03 | 03 | 914 | +50/-0 |
| 4232-25M09F-06 | 06 | 1829 | +75/-0 |
| 4232-25M09F-10 | 10 | 3048 | +75/-0 |
| 4232-25M09F-15 | 15 | 4572 | +75/-0 |

| NET MECHANISM Corp | | | |
|--------------------|----------|---------|-------|
| www.cabling-ol.net | | | |
| SCALE | NONE | | REV B |
| UNIT | MM | | |
| SHEET | 1/1 | DWG NO. | |
| DATE | 06/11/05 | | |
| TITLE | | | |
| DB25M TO DB9F | | | |
| PART NO. | | | |
| 4232-25M09F-XX | | | |