

NOTE:

1. CABLE: 28AWG X 9C, AL-FOIL SHIELDED WITH DRAIN WIRE, UL2464,BEIGE (BG-02) PVC JACKET  $\phi 5.0 \pm 0.15$ mm.
2. CONNECTOR: P1:D-SUB 9PIN FEMALE:SOLDER TYPE,GOLD FLASH CONTACTS.  
P2:D-SUB 25PIN MALE:SOLDER TYPE,GOLD FLASH CONTACTS.
3. THUMB SCREW TO BE MOLDED BEIGE(BG-02)PVC, UL94V-0.
4. SHIELDING: AL-FOIL TAPE COVER PREMOLD AND 100% CONTACT WITH SHELL.
5. ALL HOOD: MOLDED BEIGE(BG-02) PVC.UL94V-0.
6. TESTING:100% ELECTRICAL TESTING.


PIN OUT

P1	P2
1	8
2	3
3	2
4	20
5	7
6	6
7	4
8	5
9	22

(DRAIN WIRE)SHELL ——— SHELL

CHART:

P/N	XX(FT)	L(MM)	TOLERANCE(MM)
4232-25M09F-03	03	914	+50/-0
4232-25M09F-06	06	1829	+75/-0
4232-25M09F-10	10	3048	+75/-0
4232-25M09F-15	15	4572	+75/-0
4232-25M09F-33	33	10058	+150/-0
4232-25M09F-50	50	15240	+300/-0

NET MECHANISM Corp www.cabling-ol.net				
SCALE	NONE		REV	C
UNIT	MM			
SHEET	1/1	DWG NO.		
DATE	01/17/13			
TITLE DB25M TO DB9F				
PART NO. 4232-25M09F-XX				