



NOTE:

1. CABLE: 28AWG X 9C, AL-FOIL SHIELDED WITH DRAIN WIRE, UL2464,BEIGE (BG-02) PVC JACKET $\phi 5.0 \pm 0.15$ mm.
2. CONNECTOR: P1:D-SUB 9PIN FEMALE:SOLDER TYPE,GOLD FLASH CONTACTS.
P2:D-SUB 25PIN MALE:SOLDER TYPE,GOLD FLASH CONTACTS.
3. THUMB SCREW TO BE MOLDED BEIGE(BG-02)PVC, UL94V-0.
4. SHIELDING: AL-FOIL TAPE COVER PREMOLD AND 100% CONTACT WITH SHELL.
5. ALL HOOD: MOLDED BEIGE(BG-02) PVC.UL94V-0.
6. TESTING:100% ELECTRICAL TESTING.

PIN OUT

P1	P2
1	8
2	3
3	2
4	20
5	7
6	6
7	4
8	5
9	22

(DRAIN WIRE)SHELL—— SHELL

CHART:

P/N	XX(FT)	L(MM)	TOLERANCE(MM)
4232-25M09F-03UU	03	914	+50/-0
4232-25M09F-06UU	06	1829	+75/-0
4232-25M09F-10UU	10	3048	+75/-0
4232-25M09F-15UU	15	4572	+75/-0
4232-25M09F-33UU	33	10058	+150/-0
4232-25M09F-50UU	50	15240	+300/-0

NET MECHANISM Corp				
www.cablng-ol.net				
SCALE	NONE		REV	C
UNIT	MM			
SHEET	1/1	DWG NO.		
DATE	01/17/13			
TITLE				
DB25M TO DB9F				
PART NO.				
4232-25M09F-XXUU				