



P/N	X(M)	L(MM)	TOLERANCE(MM)
488-008	0.8	800	+50/-0
488-015	1.5	1500	+75/-0
488-03	3	3000	+75/-0
488-05	5	5000	+150/-0
488-08	8	8000	+150/-0

NOTE

- 1.CABLE:UL 2464 (IEEE 488 B TYPE),26AWG\*12PAIRS+AL-FOIL+DRAIN+BRAID(90%),JACKET:PVC HOOT TYPE, COLOR:GRAY(GY-08),OD=10.5±0.2mm
- 2.CONNECTOR: P1 AND P2:CENTRONICS 24PIN M/F ADAPTER, SOLDER TYPE,GOLD FLASH CONTACTS,BLACK PBT INSULATION.
- 3.METAL THUMB SCREW.
- 4"E"TYPE MATAL "SCREW CLIP"(NICKEL PLATED).
- 5.SHIELDING:METAL-CAN COVER 4 POINTS SOLDER TO SHELL.
6. ALL HOOD:MOLDED PVC GRAY(GY02).
- 7.TESTING:100% ELECTRICAL TEST.
- 8.MOLD NO.:CN24-01,CN24-N01.

NET MECHANISM Corp www.cabling-ol.net				
SCALE	NONE		REV	B
UNIT	MM			
SHEET	1/1	DWG NO.		
DATE	07/05/13			
TITLE	CN24 M/F TO CN24 M/F			
PART NO.	488-XX			