



ANOTE:

1. CABLE: 28AWG X 9C, AL-FOIL SHIELDED WITH DRAIN WIRE, UL2464,BEIGE (BG-02) PVC JACKET $\phi 5.0 \pm 0.15$ mm.
2. CONNECTOR: P1 & P2: D-SUB 9PIN FEMALE: SOLDER TYPE, GOLD FLASH CONTACTS. UL RECOGNIZED.
3. THUMB SCREW TO BE MOLDED BEIGE(BG-02)PVC, UL94V-0.
4. SHIELDING: AL-FOIL TAPE COVER PREMOLD AND 100% CONTACT WITH SHELL.
5. ALL HOOD: MOLDED BEIGE(BG-02) PVC.UL94V-0.
6. TESTING:100% ELECTRICAL TESTING.

PIN OUT

P1	P2
1	1
2	2
3	3
4	4
5	5
6	6
7	7
8	8
9	9

(DRAIN WIRE)SHELL ——— SHELL

CHART:

P/N	XX(FT)	L(MM)	TOLERANCE(MM)
6232-9F9F-03	3	914	+50/-0
6232-9F9F-06	6	1829	+75/-0
6232-9F9F-10	10	3048	+75/-0
6232-9F9F-15	15	4572	+75/-0

NET MECHANISM Corp www.cabling-ol.net				
SCALE	NONE		REV	B
UNIT	MM			
SHEET	1/1	DWG NO.		
DATE	06/11/05			
TITLE		DB9F TO DB9F		
PART NO.		6232-9F9F-XX		