



NOTE:

1. CABLE: 28AWG X 9C, AL-FOIL SHIELDED WITH DRAIN WIRE, UL2464,BEIGE(BG-02) PVC JACKET $\phi 5.0 \pm 0.15$ mm.
2. CONNECTOR:P1:D-SUB 9PIN MALE: SOLDER TYPE,BLACK PBT INSULATION,GOLD FLASH CONTACTS.SHELL NICKEL PLATED ON TOP AND TIN PLATED ON BOTTOM.WITH HEX NUT.
P2:D-SUB 9PIN FEMALE: SOLDER TYPE,BLACK PBT INSULATION,GOLD FLASH CONTACTS.SHELL NICKEL PLATED ON TOP AND TIN PLATED ON BOTTOM.
3. HEX NUT:# 4-40UNC.
4. THUMB SCREW TO BE MOLDED BEIGE(BG-02)PVC, UL94V-0.
5. SHIELDING: AL-FOIL TAPE COVER PREMOLD AND 100% CONTACT WITH SHELL.
6. ALL HOOD: MOLDED BEIGE(BG-02) PVC.UL94V-0.
7. TESTING:100% ELECTRICAL TESTING.

PIN OUT

P1	P2
1	1
2	2
3	3
4	4
5	5
6	6
7	7
8	8
9	9

(DRAIN WIRE)SHELL ——— SHELL

CHART:

P/N	xx	**	L	T
6232-9M9F-03NU	3	03	914	+50/-0
6232-9M9F-06NU	6	06	1829	+75/-0
6232-9M9F-10NU	10	10	3048	+75/-0
6232-9M9F-15NU	15	15	4572	+75/-0

NET MECHANISM Corp www.cabling-ol.net				
SCALE	NONE		REV	B
UNIT	MM			
SHEET	1/1	DWG NO.		
DATE	06/11/05			
TITLE		DB9M TO DB9F		
PART NO.		6232-9M9F-XXNU		