

NOTE:

1. CABLE: 28AWG X 9C, AL-FOIL SHIELDED WITH DRAIN WIRE, UL2464,BEIGE(BG-02) PVC JACKET $\varnothing 5.0 \pm 0.15$ mm.
2. CONNECTOR: P1:D-SUB 9PIN MALE:SOLDER TYPE,GOLD FLASH CONTACTS.UL RECOGNIZED. WITH HEX NUT.
P2:D-SUB 9PIN FEMALE:SOLDER TYPE,GOLD FLASH CONTACTS.UL RECOGNIZED.

⚠️ HEX NUT:# 4-40UNC.

⚠️ THUMB SCREW TO BE MOLDED BEIGE(BG-02)PVC, UL94V-0.

5. SHIELDING: AL-FOIL TAPE COVER PREMOLD AND 100% CONTACT WITH SHELL.

6. ALL HOOD: MOLDED BEIGE(BG-02) PVC.UL94V-0.


7. TESTING:100% ELECTRICAL TESTING.

PIN OUT

P1	P2
1	1
2	2
3	3
4	4
5	5
6	6
7	7
8	8
9	9
(DRAIN WIRE)SHELL	SHELL

CHART:

P/N	XX(FT)	L(MM)	TOLERANCE(MM)
6232-9M9F-03NU	3	914	+50/-0
6232-9M9F-06NU	6	1829	+75/-0
6232-9M9F-10NU	10	3048	+75/-0
6232-9M9F-15NU	15	4572	+75/-0

NET MECHANISM Corp www.cabling-ol.net			
SCALE	NONE		REV B
UNIT	MM		
SHEET	1/1	DWG NO.	
DATE	06/11/05		
TITLE DB9M TO DB9F			
PART NO. 6232-9M9F-XXNU			