



P/N	XX(FT)	L(MM)	TOLERANCE(MM)
6232-IC-9F9F-06	06	1829	+75/-0
6232-IC-9F9F-10	10	3048	+75/-0
6232-IC-9F9F-15	15	4572	+75/-0

NOTE:

- CABLE: 28AWG X 7C, AL-FOIL SHIELDED WITH DRAIN WIRE, UL2464, BEIGE (BG-02) PVC JACKET $\phi 5.0 \pm 0.15$ mm.
- CONNECTOR: P1 & P2: D-SUB 9PIN FEMALE: SOLDER TYPE, GOLD FLASH CONTACTS. UL RECOGNIZED.
- THUMB SCREW TO BE MOLDED BLACK PVC, UL94V-0.
- SHIELDING: AL-FOIL TAPE COVER PREMOLD AND 100% CONTACT WITH SHELL.
- ALL HOOD: MOLDED BLACK PVC. UL94V-0.
- TESTING: 100% ELECTRICAL TESTING.
- MOLD NO: P1 & P2: DB9-01.

NET MECHANISM Corp				
www.cabling-ol.net				
SCALE	NONE		REV	A
UNIT	MM			
SHEET	1/1	DWG NO.		
DATE	06/17/05			
TITLE				
DB 9F TO DB9F				
PART NO.				
6232-IC-9F9F-XX				