



PIN OUT

P1	P2
2	3
3	2
4	6
5	5
6	4
7	8
8	7
SHELL	SHELL(DRAIN WIRE)

P/N	XX(FT)	L(MM)	TOLERANCE(MM)
6232-IC-9F9F-06	06	1829	+75/-0
6232-IC-9F9F-10	10	3048	+75/-0
6232-IC-9F9F-15	15	4572	+75/-0
6232-IC-9F9F-33	33	10058	+150/-0
6232-IC-9F9F-50	50	15240	+300/-0

NOTE:

- CABLE: 28AWG X 7C, AL-FOIL SHIELDED WITH DRAIN WIRE, UL2464,BEIGE(BG-02) PVC JACKET $\phi 5.0 \pm 0.15$ mm.
- CONNECTOR: P1 & P2: D-SUB 9PIN FEMALE: SOLDER TYPE, GOLD FLASH CONTACTS.
- THUMB SCREW TO BE MOLDED BLACK PVC, UL94V-0.
- SHIELDING: AL-FOIL TAPE COVER PREMOLD AND 100% CONTACT WITH SHELL.
- ALL HOOD: MOLDED BLACK PVC,UL94V-0.
- TESTING:100% ELECTRICAL TESTING.
- MOLD NO:P1&P2:DB9-01.

NET MECHANISM Corp				
www.cabling-ol.net				
SCALE	NONE		REV	B
UNIT	MM			
SHEET	1/1	DWG NO.		
DATE	01/17/13			
TITLE		DB 9F TO DB9F		
PART NO.		6232-IC-9F9F-XX		