



PIN OUT

P1	P2	
1	1	BLACK
2	2	BROWN
3	3	RED
4	4	ORANGE
5	5	YELLOW
6	6	GREEN
7	7	BLUE
8	8	PURPLE
9	9	GRAY

(DRAIN WIRE)SHELL ——— SHELL

ANOTE:

1. CABLE: 24AWG X 9C, AL-FOIL SHIELDED WITH DRAIN WIRE AND BRAID, UL2448, GRAY(GY-02) PVC JACKET $\phi 7.0 \pm 0.15$ mm.
2. CONNECTOR: P1 & P2: D-SUB 9PIN FEMALE: SOLDER TYPE, GOLD FLASH CONTACTS. UL RECOGNIZED.
3. THUMB SCREW TO BE MOLDED GRAY(GY-02)PVC, UL94V-0.
4. SHIELDED: COPPER FOIL TAPE COVER PREMOLD AND 360° SOLDER TO CONNECTOR SHELL AND CABLE BRAID.
5. ALL HOOD: MOLDED GRAY(GY-02) PVC.UL94V-0.
6. TESTING:100% ELECTRICAL TESTING.
7. MOLD NO.:DB9-01,DB9-N01.

CHART:

P/N	L(MM)	TOLERANCE(MM)
7232-9F9F-M30	30000	+300/-0
7232-9F9F-M50	50000	+500/-0
7232-9F9F-M75	75000	+500/-0
7232-9F9F-M100	100000	+500/-0
7232-9F9F-M150	150000	+500/-0

NET MECHANISM Corp
www.cabling-ol.net

SCALE	NONE		REV	A
UNIT	MM			
SHEET	1/1	DWG NO.		
DATE	03/05/08			
TITLE	DB9F TO DB9F			
PART NO.	7232-9F9F-MXX			