



ANOTE:

1. CABLE: 24AWG X 9C, AL-FOIL SHIELDED WITH DRAIN WIRE AND BRAID, UL2448,GRAY(GY-02) PVC JACKET $\phi 7.0 \pm 0.15$ mm.
- 2.CONN.:P1,P2:D-SUB 9PIN FEMALE:SOLDER TYPE,BLACK PBT INSULATION, GOLD FLASH CONTACTS,SHELL NICKEL PLATED ON TOP AND TIN PLATED ON BOTTOM.
3. $\phi 1.0 \times 10$ MM BLACK HEAT SHRINK TUBING.
4. $\phi 8.0 \times 15$ MM BLACK HEAT SHRINK TUBING.
5. $\phi 1.5 \times 30$ MM BLACK HEAT SHRINK TUBING.
- 6.D-SUB 9P HOOD.
- 7.TESTING:100% ELECTRICAL TEST.

PIN OUT

P1	P2	
1	1	BLACK
2	2	BROWN
3	3	RED
4	4	ORANGE
5	5	YELLOW
6	6	GREEN
7	7	BLUE
8	8	PURPLE
9	9	GRAY
SHELL		SHELL(DRAIN+BRAID)

CHART:

P/N	L(MM)	TOLERANCE(MM)
7232-9F9F-M30	30000	+300/-0
7232-9F9F-M50	50000	+500/-0
7232-9F9F-M75	75000	+500/-0
7232-9F9F-M100	100000	+500/-0
7232-9F9F-M150	150000	+500/-0

B	CHANGE MOLD TYPE FOR ASS'Y HOOD	08/20/10
A	INITIAL RELEASE	03/05/08
REV	DESCRIPTION OF CHANGE	DATE

NET MECHANISM Corp			
www.cabling-ol.net			
SCALE	NONE		REV
UNIT	MM		B
SHEET	1/1	DWG NO.	
DATE	08/20/10		
TITLE		DB9F TO DB9F	
PART NO.		7232-9F9F-MXX	