


NOTE:

1. CABLE: 28AWG X 8C, AL-FOIL SHIELDED WITH DRAIN WIRE, UL2464,BEIGE(BG-02)
PVC JACKET $\phi 5.0 \pm 0.15$ mm.
2. CONNECTOR: P1:D-SUB 9PIN FEMALE:SOLDER TYPE,GOLD FLASH CONTACTS.
INSULATION:BLACK,SHELL NICKEL PLATED ON TOP AND TIN PLATED ON BOTTOM.
P2:D-SUB 25PIN MALE:SOLDER TYPE,GOLD FLASH CONTACTS.
INSULATION:BLACK,SHELL NICKEL PLATED ON TOP AND TIN PLATED ON BOTTOM.
3. THUMB SCREW TO BE MOLDED BEIGE(BG-02)PVC, UL94V-0.
4. SHIELDING: AL-FOIL TAPE COVER PREMOLD AND 100% CONTACT WITH SHELL.
5. ALL HOOD: MOLDED BEIGE(BG-02) PVC.UL94V-0.
6. TESTING:100% ELECTRICAL TESTING.
7. MOLD P/N: P1:DB9-01,DB9-N01; P2:DB25-01,DB25-N01.



(DRAIN WIRE)SHELL ——— SHELL

CHART:

P/N	xx(FT)	L(MM)	TOLERANCE(MM)
9232-25M09F-03	03	914	+50/-0
9232-25M09F-06	06	1829	+75/-0
9232-25M09F-10	10	3048	+75/-0
9232-25M09F-15	15	4572	+75/-0
9232-25M09F-33	33	10058	+150/-0
9232-25M09F-50	50	15240	+300/-0

NET MECHANISM Corp			
www.cabling-ol.net			
SCALE	NONE		REV
UNIT	MM		C
SHEET	1/1	DWG NO.	
DATE	01/17/13		
TITLE	DB25M TO DB9F		
PART NO.	9232-25M09F-XX		