



WIRE CONNECTION

WIRE COLOR	P1	PAIRS	P2
WHITE/ORANGE	1	———	1
ORANGE	2	———	2
WHITE/GREEN	3	———	3
BLUE	4	———	4
WHITE/BLUE	5	———	5
GREEN	6	———	6
WHITE/BROWN	7	———	7
BROWN	8	———	8

REMARK:

1. CABLE: CAT.6 UTP 24AWG*4P (7/0.205, BARE COPPER INSULATION: PE)+CROSS JACKET: WHITE (WH-02) PVC, OD: 6.2±0.2MM,
2. CONN.: P1 & P2: 8P8C JACK, PIN: GOLD PLATED, INSULATION: BLACK.
3. NUT: M3.0 NUT EMBEDDED.
4. HOOD: MOLDING WHITE (WH-02) PVC.
5. CABLE ASS'Y MUST PASS CONTINUITY TEST.

P/N	L	T
AC6FF-PL150	150	+25/-0
AC6FF-PL1000	1000	+75/-0
AC6FF-PL3000	3000	+75/-0

NET MECHANISM Corp www.cabling-ol.net			
SCALE	NONE		REV B
UNIT	MM		
SHEET	1/1	DWG NO.	
DATE	11/13/13		
TITLE CAT6 8P8C JACK TO 8P8C JACK CABLE			
PART NO. AC6FF-PLXXXX			