



NOTE:

1. CABLE: UL2919 28AWG(7/0.127)*3COAX(OFC)+PAPER+JACKET.JACKET COLOR: BLACK MATT PVC AND OD=7.0±0.15MM.
2. CONNECTOR: P1: HIGH DENSITY D-SUB 15PIN MALE: SOLDER TYPE, GOLD FLASH CONTACTS, 9PIN UNLOADED,PBT BLACK.GOLD PLATED SHELL. P2,P3,P4:RCA FEMALE,INSULATION:WHITE,SHELL:GOLD PLATED.
3. THUMB SCREW TO MOLDED 25P BLACK #4-40UNC 4.0*H40.5mm.
4. STRAIN RELIEF,P1:MOLDING 45P BLACK PVC.
5. MOLDING 90P PVC.P2:GREEN,P3:BLUE,P4:RED.
6. PACKING: EACH CABLE IN A ZIP-LOCK POLY-BAG.
7. MOLD NO.:HD15-01,HD15-N01,RCA-01,RCA-N01,SR-11.

NET MECHANISM Corp www.cabling-ol.net				
SCALE	NONE		REV	A
UNIT	MM			
SHEET	1/1	DWG NO.		
DATE	04/04/08			
TITLE HDB15M TO RCAF*3				
PART NO. ADC-HD15M-3RCAF-150				