

SPECIFICATION:		4P*24AWG+MYLAR+DRAIN+AL.MYLAR		CONSTRUCTION D.W.G			
ITEM		SPECIFICATION		<p>PVC JACKET AL.MYLAR MYLAR CONDUCTOR INSULATION DRAIN</p>			
CONDUCTOR	AWG	24AWG					
	MATERIAL	BARE COPPER					
	COND.SIZE	7/0.203±0.008 mm					
INSULATION	MIN.AVG.THICK	0.15 mm					
	MATERIAL	HD-PE					
	Ø .D	0.99±0.05 mm					
MYLAR	N O.	4P					
	COVERAGE	100%					
	OVERLAP	25% MIN					
DRAIN	AWG	24AWG					
	MATERIAL	TINNED COPPER					
	SIZE	7/0.20±0.008 mm×1PC					
Face Inside AL.MYLAR	COVERAGE	100%				COLOUR CODE: 1.BLUE *WHITE/BLUE 2.ORANGE*WHITE/ORANGE 3. GREEN*WHITE/GREEN 4. BROWN*WHITE/BROWN	
	OVERLAP	25% MIN					
JACKET	MIN.AVG.THICK	0.50 mm					
	MATERIAL	HALF MATT PVC					
	COLOUR	UL10464 LOW TOXIC					
	Ø .D	6.00 ± 0.15 mm					
ELECTRICAL CHARACTERISTICS 1. Rating : TEMP 60°C 2. Conductor Resistance: AT 20°C MAX 24AWG: 93.25Ω/km;				MARKING			
				E188601 (UL) TYPE CM LL84201 CSA TYPE CMG FT4 CAT5E PATCH CABLE TO TIA/EIA 568A 4STP 24AWG STRANDED			
				REMARK			
				PART NO.			
APPROVED				CUSTOMER			
CHECKED				REV			
DRAWING		LXY		DATE			
				A			
				2004/5/28			