


WIRE LIST

P1	P2	
1	1	CENTER
2	2	OUTER

REMARK:

- 1.CONSTRUCTION: SHAPE AND DIMENSIONS SUBJECT TO ATTACHED CHARTREGULATION.APPEARANCE:EVERY PART SHOULD BE FINISHED NOT TO DILAPIDTION. CRACK AND BAD FLATING.
- 2.P1: BNC FEMALE,NICKEL PLATED SHELL,NICKEL FLASH CONTACTS AND P2:RCA MALE,NICKEL PLATED SHELL,NICKEL FLASH CONTACTS.
- 3.ADAPTER INSERION EXTRSCTION: FORLE 3Kg TO 12Kg.
- 4.ELECTRONIC CHARCTERISTICS: CONTACT RESISTANCE:20MΩ  
INSULATION RESISTANC:20MΩ WITHSTAND VOLTAGE AC:200V DC:250V  
CURRENT RATING AC:100V/0.5A DC:150V/1A
- 5.OPERATING TEMPERATURE-30°C-+60°C AND ELECTRICAL LIFE IS 5000 TIMES INSERTING LEXTRACTING CIT FALL LOAD.
- 6.NO OVERMOLD.

NET MECHANISM Corp				
www.cabling-ol.net				
SCALE	NONE		REV	A
UNIT	MM			
SHEET	1/1	DWG NO.		
DATE	06/17/05			
TITLE		BNC/F TO RCA/M		
PART NO.		BNCF-RCAM		