



P/N	X(M)	L(MM)	TOLERANCE(MM)
BNCM-RCAF-1.5	1.5	1500	+50/-0
BNCM-RCAF-2	2	2000	+75/-0
BNCM-RCAF-3	3	3000	+75/-0
BNCM-RCAF-5	5	5000	+75/-0

PIN OUT:

P1 P2

1 ——— 1

shell ——— shell

NOTE:

1. NON-UL [1C*26AWG(7/0.16)+AL/MYLAR+SPIRAL]+PVC JACKET
COLOR BLACK MATT OD=6.0±□0.15MM(75ohm) P/N: B-AV1F-BK-75
2. CONN.: P1: BNC MALE, GOLD FLASH CONTACTS, 75 OHM
P2: RCA JACK, SHELL GOLD PLATED 1.5u".
3. HOOD: 45P PVC BLACK.
4. MOLD 45P PVC BLACK.
5. TESTING: 100% ELECTRICAL TEST.
6. PACKING: EACH CABLE IN A POLY-BAG.

NET MECHANISM Corp www.cabling-ol.net				
SCALE	NONE		REV	A
UNIT	MM			
SHEET	1/1	DWG NO.		
DATE	06/21/05			
TITLE		BNCM TO RCAF		
PART NO.		BNCM-RCAF-XX		