



WIRE LIST

P1		P2	
1	_____	1	_____ CENTER
2	_____	2	_____ OUTER

REMARK:

- 1.CONSTRUCTION: SHAPE AND DIMENSIONS SUBJECT TO ATTACHED CHARTREGULATION.APPEARANCE:EVERY PART SHOULD BE FINISHED NOT TO DILAPIDTION. CRACK AND BAD FLATING.
- 2.P1:BNC MALE,NICKEL PLATED SHELL,NICKEL PLATED CONTACTS AND P2:RCA FEMALE,NICKEL PLATED SHELL.
- 3.ADAPTER INSERION EXTRSCTION: FORLE 0.5Kg TO 2.0Kg.
- 4.ELECTRONIC CHARCTERISTICS: CONTACT RESISTANCE:30M Ω
INSULATION RESISTANC: 50MΩ WITHSTAND VOLTAGE AC:150V DC:300V
CURRENT RATING AC:150V/0.5A DC:250V/1A
- 5.OPERATING TEMPERATURE-30°C-+60°C AND ELECTRICAL LITE IS 5000 TIMES INSERTING LEXTRACTING CIT FALL LOAD.
- 6.NO MOLDING.

NET MECHANISM Corp www.cabling-ol.net				
SCALE	NONE		REV	A
UNIT	MM			
SHEET	1/1	DWG NO.		
DATE	06/17/05	TITLE		
		BNC/M TO RCA/F		
PART NO.		BNCM-RCAF		