


| P/N            | X(M) | L(MM) | TOLERANCE(MM) |
|----------------|------|-------|---------------|
| BNCPP-174U0050 | 0.5  | 500   | +50/-0        |
| BNCPP-174U0100 | 1    | 1000  | +75/-0        |
| BNCPP-174U0150 | 1.5  | 1500  | +75/-0        |
| BNCPP-174U0200 | 2    | 2000  | +75/-0        |
| BNCPP-174U0300 | 3    | 3000  | +75/-0        |
| BNCPP-174U0500 | 5    | 5000  | +150/-0       |

PIN OUT :



NOTE:

- 1.CABLE:RG174/U 26AWGx1C(7/0.16 TINNED COPPER)+PE INSULATION+ BRAID(16\*4/0.12),PVC JACKET,COLOR:BLACK,ø3.0±0.15mm.
- 2.CONN.:P1,P2: BNC MALE, GOLD FLASH CONTACTS, 50 OHM.(RG174U)
- 3.MOLD 45P PVC BLACK.
- 4.TESTING:100% ELECTRICAL TEST.
- 5.PACKING:EACH CABLE IN A POLY-BAG.

|                    |          |                |     |   |
|--------------------|----------|----------------|-----|---|
| NET MECHANISM Corp |          |                |     |   |
| www.cabling-ol.net |          |                |     |   |
| SCALE              | NONE     |                | REV | B |
| UNIT               | MM       |                |     |   |
| SHEET              | 1/1      | DWG NO.        |     |   |
| DATE               | 09/26/13 |                |     |   |
| TITLE              |          | BNC M TO BNC M |     |   |
| PART NO.           |          | BNCPP-174UXXXX |     |   |