



P/N	X(M)	L(MM)	TOLERANCE(MM)
BNCPP-174U0050	0.5	500	+25/-0
BNCPP-174U0100	1	1000	+25/-0
BNCPP-174U0150	1.5	1500	+50/-0
BNCPP-174U0200	2	2000	+50/-0
BNCPP-174U0300	3	3000	+50/-0
BNCPP-174U0500	5	5000	+50/-0

PIN OUT :



NOTE:

- 1.CABLE:RG174/U 26AWGx1C(7/0.16 TINNED COPPER)+PE INSULATION+ BRAID(16\*4/0.12),PVC JACKET,COLOR:BLACK,ø3.0±0.15mm.
- 2.CONN.:P1,P2: BNC MALE, GOLD FLASH CONTACTS, 50 OHM.(RG174U)
- 3.MOLD 45P PVC BLACK.
- 4.TESTING:100% ELECTRICAL TEST.
- 5.PACKING:EACH CABLE IN A POLY-BAG.

NET MECHANISM Corp www.cabling-ol.net				
SCALE	NONE		REV	A
UNIT	MM			
SHEET	1/1	DWG NO.		
DATE	11/13/04			
TITLE	BNC/M TO BNC/M			
PART NO.	BNCPP-174UXXXX			