



P/N	X(M)	L(MM)	TOLERANCE(MM)
BNCPP-59BU0050	0.5	500	+50/-0
BNCPP-59BU0100	1	1000	+75/-0
BNCPP-59BU0150	1.5	1500	+75/-0
BNCPP-59BU0200	2	2000	+75/-0
BNCPP-59BU0300	3	3000	+75/-0
BNCPP-59BU0500	5	5000	+150/-0
BNCPP-59BU1000	10	10000	+150/-0
BNCPP-59BU1500	15	15000	+300/-0
BNCPP-59BU2000	20	20000	+300/-0
BNCPP-59BU3000	30	30000	+300/-0

PIN OUT :



NOTE:

- 1.CABLE:RG59B/U CONDUCTOR:1/0.58 BARE COPPER)+PE INSULATION+ BRAID(16*7/0.12),PVC JACKET,COLOR:BLACK(BK), $\phi 6.0 \pm 0.15$ mm.
- 2.CONN.:P1,P2: BNC MALE, GOLD FLASH CONTACTS, 75 OHM.(RG59U)
- 3.MOLD 45P PVC BLACK(BK).
- 4.TESTING:100% ELECTRICAL TEST.
- 5.PACKING:EACH CABLE IN A POLY-BAG.

NET MECHANISM Corp				
www.cabling-ol.net				
SCALE	NONE		REV	B
UNIT	MM			
SHEET	1/1	DWG NO.		
DATE	11/01/13			
TITLE BNC/M 75ohm TO BNC/M				
PART NO. BNCPP-59BUXXXX				