



P/N	X(FT)	L(MM)	TOLERANCE(MM)
BNCPP-HFC-03	3	914	+50/-0
BNCPP-HFC-06	6	1829	+75/-0
BNCPP-HFC-10	10	3048	+75/-0

PIN OUT :



NOTE:

- 1.CABLE:BELDEN1505F RG59/U CONDUCTOR:22AWG STRANDED(BARE COMPACTED COPPER)  
+PE INSULATION+DOUBLE TINNED COPPER BRAID SHIELD,PVC JACKET,COLOR:BLACK,  
OD:0.242IN( $\phi 6.15 \pm 0.15$ mm) IMPEDANCE:75 OHM.
- 2.CONN.:P1,P2: BNC MALE, GOLD FLASH CONTACTS, 75 OHM.(RG59U)
- 3.BNC HOOD:45P PVC BLACK.
- 4.TESTING:100% ELECTRICAL TEST.
- 5.PACKING:EACH CABLE IN A POLY-BAG.

NET MECHANISM Corp www.cabling-ol.net				
SCALE	NONE		REV	A
UNIT	MM			
SHEET	1/1	DWG NO.		
DATE	06/17/05			
TITLE BNC/M TO BNC/M 75 OHM				
PART NO. BNCPP-HFC-XX				