


P1 CN14M

P2 CN14M

PIN OUT

P1	P2	Color
1	1	BK
8	8	BK/WH
2	2	BR
9	9	BR/WH
3	3	RD
10	10	RD/WH
4	4	OR
11	11	OR/WH
5	5	YL
12	12	YL/BK
6	6	GN
13	13	GN/WH
7	7	BL
14	14	BL/WH

SHELL ————— SHELL(BRAID + DRAIN WIRE)



P/N	X(M)	L(MM)	TOLERANCE(MM)
C14PP-M0050	0.5	500	+50/-0
C14PP-M0100	1	1000	+75/-0
C14PP-M0150	1.5	1500	+75/-0
C14PP-M0200	2	2000	+75/-0
C14PP-M0300	3	3000	+75/-0
C14PP-M0500	5	5000	+150/-0

MERCHANDISE MOQ	EACH 50PCS
LEAD TIME	14 DAY
CABLE MOQ	EACH 3000M
CONNECTOR MOQ	EACH 1000PCS

NET MECHANISM Corp
www.cabling-ol.net

SCALE	NONE		REV	B
UNIT	MM			
SHEET	1/1	DWG NO.		
DATE	09/26/13			

TITLE CN14 M TO CN14 M

PART NO. C14PP-MXXXX

NOTE:

- CABLE: UL2464 28AWG*7P+AEB. PVC JACKET BGIGE(BG02),OD:7.0±0.15mm.
- CONNECTOR: P1 AND P2 : CENTRONICS 14PIN MALE: SOLDER ASSY TRADITION TYPE, GOLD FLASH CONTACTS. BLUE PBT INSULATION,W/METAL SHELL AND THIMBLE(OD:10mm).
- PACKING: EACH CABLE IN A ZIP-LOCK POLY-BAG.
LABEL (WHITE BACKGROUND WITH BLACK LETTERS) TO BE STAMPED ON POLYBAG.
- 100% ELECTRICAL TESTING.