



P1 CN14F
FEMALE BAIL LOCK HARDWARE(X2)

PIN OUT

P1	— 0 —	OPEN
1	— 0 —	BK
8	— 0 —	BK/WH
2	— 0 —	BR
9	— 0 —	BR/WH
3	— 0 —	RD
10	— 0 —	RD/WH
4	— 0 —	OR
11	— 0 —	OR/WH
5	— 0 —	YL
12	— 0 —	YL/BK
6	— 0 —	GN
13	— 0 —	GN/WH
7	— 0 —	BL
14	— 0 —	BL/WH
SHELL	— — —	SHELL(BRAID+DRAIN)
	— 8 —	> 1 PAIR

P/N	X(M)	L(MM)	TOLERANCE(MM)
C14S-M0050	0.5	500	+25/-0
C14S-M0100	1	1000	+25/-0
C14S-M0150	1.5	1500	+50/-0
C14S-M0200	2	2000	+50/-0
C14S-M0300	3	3000	+50/-0
C14S-M0500	5	5000	+50/-0

NOTE:

- CABLE: UL2464 28AWG*7P+AEB. PVC JACKET BGIG(BG-02), OD:7.0±0.15MM.
- CONNECTOR:P1:CENTRONICS 14PIN FEMALE: SOLDER ASSY NEW TYPE, GOLD FLASH CONTACTS. BLUE PBT INSULATION, W/METAL SHELL AND THIMBLE(OD:10MM).
- PACKING: EACH CABLE IN A ZIP-LOCK POLY-BAG.
LABEL (WHITE BACKGROUND WITH BLACK LETTERS) TO BE STAMPED ON POLYBAG.
- 100% ELECTRICAL TESTING.

NET MECHANISM Corp				
www.cabling-ol.net				
SCALE	NONE		REV	A
UNIT	MM			
SHEET	1/1	DWG NO.		
DATE	11/13/04			
TITLE	CN14F TO OPEN			
PART NO.	C14S-MXXXX			