



P1 CN14F
FEMALE BAIL LOCK HARDWARE(X2)

PIN OUT

| | | |
|-------|-------|--------------------|
| P1 | — 0 — | OPEN |
| 1 | — 0 — | BK |
| 8 | — 0 — | BK/WH |
| 2 | — 0 — | BR |
| 9 | — 0 — | BR/WH |
| 3 | — 0 — | RD |
| 10 | — 0 — | RD/WH |
| 4 | — 0 — | OR |
| 11 | — 0 — | OR/WH |
| 5 | — 0 — | YL |
| 12 | — 0 — | YL/BK |
| 6 | — 0 — | GN |
| 13 | — 0 — | GN/WH |
| 7 | — 0 — | BL |
| 14 | — 0 — | BL/WH |
| SHELL | — — — | SHELL(BRAID+DRAIN) |
| | — 8 — | > 1 PAIR |

| P/N | X(M) | L(MM) | TOLERANCE(MM) |
|------------|------|-------|---------------|
| C14S-M0050 | 0.5 | 500 | +25/-0 |
| C14S-M0100 | 1 | 1000 | +25/-0 |
| C14S-M0150 | 1.5 | 1500 | +50/-0 |
| C14S-M0200 | 2 | 2000 | +50/-0 |
| C14S-M0300 | 3 | 3000 | +50/-0 |
| C14S-M0500 | 5 | 5000 | +50/-0 |

NOTE:

- CABLE: UL2464 28AWG*7P+AEB. PVC JACKET BGIGE(BG-02), OD:7.0±0.15MM.
- CONNECTOR:P1:CENTRONICS 14PIN FEMALE: SOLDER ASSY NEW TYPE, GOLD FLASH CONTACTS. BLUE PBT INSULATION, W/METAL SHELL AND THIMBLE(OD:10MM).
- PACKING: EACH CABLE IN A ZIP-LOCK POLY-BAG.
LABEL (WHITE BACKGROUND WITH BLACK LETTERS) TO BE STAMPED ON POLYBAG.
- 100% ELECTRICAL TESTING.

| | | | | |
|--|---------------|---------|-----|---|
| NET MECHANISM Corp www.cabling-ol.net | | | | |
| SCALE | NONE | | REV | A |
| UNIT | MM | | | |
| SHEET | 1/1 | DWG NO. | | |
| DATE | 11/13/04 | | | |
| TITLE | CN14F TO OPEN | | | |
| PART NO. | C14S-MXXXX | | | |