

P1 CN24M

PIN OUT

P2 CN24F

| | | | | | | | |
|-------|-------|---------------------------|-------|----|-------|----|-------------|
| P1 | ————— | P2 | | P1 | ————— | P2 | |
| 1 | —○— | 1 | BK | 8 | —○— | 8 | PP |
| 13 | —○— | 13 | BK/WH | 20 | —○— | 20 | PP/WH |
| 2 | —○— | 2 | BR | 9 | —○— | 9 | GY |
| 14 | —○— | 14 | BR/WH | 21 | —○— | 21 | GY/BK |
| 3 | —○— | 3 | RD | 10 | —○— | 10 | WH |
| 15 | —○— | 15 | RD/WH | 22 | —○— | 22 | OR/BK |
| 4 | —○— | 4 | OR | 11 | —○— | 11 | PK |
| 16 | —○— | 16 | OR/WH | 23 | —○— | 23 | RD/BLACK |
| 5 | —○— | 5 | YL | 12 | —○— | 12 | LIGHT GREEN |
| 17 | —○— | 17 | YL/BK | 24 | —○— | 24 | GN/BK |
| 6 | —○— | 6 | GN | | | | |
| 18 | —○— | 18 | GN/WH | | | | |
| 7 | —○— | 7 | BL | | | | |
| 19 | —○— | 19 | BL/WH | | | | |
| SHELL | ————— | SHELL(BRAID + DRAIN WIRE) | | | | | |


—○— > 1 PAIR

FEMALE BAIL LOCK HARDWARE(X2)

| P/N | X(M) | L(MM) | TOLERANCE(MM) |
|-------------|------|-------|---------------|
| C24PS-M0050 | 0.5 | 500 | +25/-0 |
| C24PS-M0100 | 1 | 1000 | +25/-0 |
| C24PS-M0150 | 1.5 | 1500 | +50/-0 |
| C24PS-M0200 | 2 | 2000 | +50/-0 |
| C24PS-M0300 | 3 | 3000 | +50/-0 |
| C24PS-M0500 | 5 | 5000 | +50/-0 |

NOTE:

- CABLE:UL2464 28AWG*12P+AEB.PVC JACKET BEIGE(BG-02),OD=8.5±0.15MM.
- CONN:P1:CENTRONICS 24PIN MALE:SOLDER ASSY TRADITION TYPE,GOLD
FLASH CONTACTS.BLUE PBT INSULATION,W/METAL SHELL AND THIMBLE(OD:10MM).
P2:CENTRONICS 24PIN FEMALE:SOLDER ASSY NEW TYPE,GOLD
FLASH CONTACTS.BLUE PBT INSULATION,W/METAL SHELL AND THIMBLE(OD:10MM).
- PACKING:EACH CABLE IN A ZIP-LOCK POLY-BAG.
LABEL(WHITE BACKGROUND WITH BLACK LETTERS)TO BE STAMPED ON POLYBAG.
- 100% ELECTRICAL TESING.

| | | | | |
|--------------------|----------|---|-----|---|
| NET MECHANISM Corp | | | | |
| www.cabling-ol.net | | | | |
| SCALE | NONE |  | REV | A |
| UNIT | MM | | | |
| SHEET | 1/1 | DWG NO. | | |
| DATE | 11/13/04 | | | |
| TITLE | | | | |
| CN24M TO CN24F | | | | |
| PART NO. | | | | |
| C24PS-MXXXX | | | | |