



P1 CN24M

PIN OUT

P2 CN24F

FEMALE BAIL LOCK HARDWARE(X2)

P1	1	P2	1	BK	P1	8	P2	8	PP		
13	13	BK/WH	20	20	PP/WH	9	9	GY	21	21	GY/BK
2	2	BR	10	10	WH	11	11	PK	22	22	OR/BK
14	14	BR/WH	11	11	PK	23	23	RD/BLACK	12	12	LIGHT GREEN
3	3	RD	12	12	LIGHT GREEN	24	24	GN/BK			
15	15	RD/WH									
4	4	OR									
16	16	OR/WH									
5	5	YL									
17	17	YL/BK									
6	6	GN									
18	18	GN/WH									
7	7	BL									
19	19	BL/WH									

> 1 PAIR

SHELL ——— SHELL(BRAID + DRAIN WIRE)

P/N	X(M)	L(MM)	TOLERANCE(MM)
C24PS-M0050	0.5	500	+25/-0
C24PS-M0100	1	1000	+25/-0
C24PS-M0150	1.5	1500	+50/-0
C24PS-M0200	2	2000	+50/-0
C24PS-M0300	3	3000	+50/-0
C24PS-M0500	5	5000	+50/-0

NOTE:

- CABLE:UL2464 28AWG*12P+AEB.PVC JACKET BEIGE(BG-02),OD=8.5±0.15MM.
- CONN:P1:CENTRONICS 24PIN MALE:SOLDER ASSY TRADITION TYPE,GOLD
FLASH CONTACTS.BLUE PBT INSULATION,W/METAL SHELL AND THIMBLE(OD:10MM).
P2:CENTRONICS 24PIN FEMALE:SOLDER ASSY NEW TYPE,GOLD
FLASH CONTACTS.BLUE PBT INSULATION,W/METAL SHELL AND THIMBLE(OD:10MM).
- PACKING:EACH CABLE IN A ZIP-LOCK POLY-BAG.
LABEL(WHITE BACKGROUND WITH BLACK LETTERS)TO BE STAMPED ON POLYBAG.
- 100% ELECTRICAL TESING.

NET MECHANISM Corp www.cabling-ol.net				
SCALE	NONE		REV	A
UNIT	MM			
SHEET	1/1	DWG NO.		
DATE	11/13/04			
TITLE	CN24M TO CN24F			
PART NO.	C24PS-MXXXX			