



CHART:

P/N	X(M)	L(MM)	TOLERANCE(MM)
C 24S-F0025	0.25	250	+15/-0
C 24S-F0050	0.5	500	+50/-0
C 24S-F0075	0.75	750	+50/-0
C 24SS-F0100	1	1000	+75/-0
C 24S-F0150	1.5	1500	+75/-0
C 24S-F0200	2	2000	+75/-0
C 24S-F0300	3	3000	+75/-0

PIN OUT

P1	RD	OPEN
1	_____	_____
2	_____	_____
3	_____	_____
4	_____	_____
5	_____	_____
•	_____	_____
•	_____	_____
•	_____	_____
24	_____	_____

Note:

- 1.CABLE:UL2651 28AWG*24C P=1.27 MM,GRAY PVC FLAT CABLE.
2. P1: CN 24F, IDC TYPE,BLUE INSULATION WITH THREE PARTS.
3. THE CABLE SHALL BE 100% ELECTRICAL TEST.

NET MECHANISM Corp				www.cabling-ol.net	
SCALE	NONE	⊕	REV	A	DWG NO.
UNIT	MM				
SHEET	1/1	TITLE			
DATE	11/13/04	CN24F IDC TO OPEN			
PART NO.		C24S-FXXXX			