


P1 CN36M

PIN OUT

P1	P2
1	1 BK
19	19 BK/WH
2	2 BR
20	20 BR/WH
3	3 RD
21	21 RD/WH
4	4 OR
22	22 OR/WH
5	5 YL
23	23 YL/BK
6	6 GN
24	24 GN/WH
7	7 BL
25	25 BL/WH
8	8 PP
26	26 PP/WH
9	9 GY
27	27 GY/BK

P1	P2
10	10 WH
28	28 OR/BK
11	11 PK
29	29 RD/BK
12	12 LIGHT GREEN
30	30 GN/BK
13	13 PK/BK
31	31 PK/RD
14	14 PK/BL
32	32 PK/GN
15	15 LIGHT BLUE
33	33 LIGHT YELLOW
16	16 LIGHT BLUE/BK
34	34 LIGHT BLUE/RD
17	17 LIGHT BLUE/BL
35	35 LIGHT BLUE/GN
18	18 GY/RD
36	36 GY/GN



SHELL ——— SHELL(BRAID + DRAIN WIRE)

FEMALE BAIL LOCK HARDWARE(X2)

P/N	X(M)	L(XX)	TOLERANCE(MM)
C36PS-M0050	0.5	500	+25/-0
C36PS-M0100	1	1000	+25/-0
C36PS-M0150	1.5	1500	+50/-0
C36PS-M0200	2	2000	+50/-0
C36PS-M0300	3	3000	+50/-0
C36PS-M0500	5	5000	+50/-0

NOTE:

- CABLE: UL2464 28AWG*18P+AEB. PVC JACKET BEIGE(BG-02), OD:9.0±0.15MM.
- CONNECTOR: P1 : CENTRONICS 36PIN MALE: SOLDER ASSY TRADITION TYPE, GOLD FLASH CONTACTS. BLUE PBT INSULATION,W/METAL SHELL AND THIMBLE(OD:13MM).
P2 : CENTRONICS 36PIN FEMALE: SOLDER ASSY NEW TYPE, GOLD FLASH CONTACTS. BLUE PBT INSULATION, W/METAL SHELL AND THIMBLE(OD:13MM).
- PACKING: EACH CABLE IN A ZIP-LOCK POLY-BAG.
LABEL (WHITE BACKGROUND WITH BLACK LETTERS) TO BE STAMPED ON POLYBAG.
- 100% ELECTRICAL TESTING.

NET MECHANISM Corp
www.cabling-ol.net

SCALE	NONE		REV	A
UNIT	MM			
SHEET	1/1	DWG NO.		
DATE	11/13/04			
TITLE		CN36M TO CN36F		
PART NO.		C36PS-MXXXX		