



P1 CN36F

FEMALE BAIL LOCK HARDWARE(X2)

PIN OUT

|    |       |       |
|----|-------|-------|
| P1 |       | OPEN  |
| 1  | — 0 — | BK    |
| 19 | — 0 — | BK/WH |
| 2  | — 0 — | BR    |
| 20 | — 0 — | BR/WH |
| 3  | — 0 — | RD    |
| 21 | — 0 — | RD/WH |
| 4  | — 0 — | OR    |
| 22 | — 0 — | OR/WH |
| 5  | — 0 — | YL    |
| 23 | — 0 — | YL/BK |
| 6  | — 0 — | GN    |
| 24 | — 0 — | GN/WH |
| 7  | — 0 — | BL    |
| 25 | — 0 — | BL/WH |
| 8  | — 0 — | PP    |
| 26 | — 0 — | PP/WH |
| 9  | — 0 — | GY    |
| 27 | — 0 — | GY/BK |

> 1 PAIR

|       |       |                    |
|-------|-------|--------------------|
| P1    |       | OPEN               |
| 10    | — 0 — | WH                 |
| 28    | — 0 — | OR/BK              |
| 11    | — 0 — | PK                 |
| 29    | — 0 — | RD/BK              |
| 12    | — 0 — | LIGHT GREEN        |
| 30    | — 0 — | GN/BK              |
| 13    | — 0 — | PK/BK              |
| 31    | — 0 — | PK/RD              |
| 14    | — 0 — | PK/BL              |
| 32    | — 0 — | PK/GN              |
| 15    | — 0 — | LIGHT BLUE         |
| 33    | — 0 — | LIGHT YELLOW       |
| 16    | — 0 — | LIGHT BLUE/BK      |
| 34    | — 0 — | LIGHT BLUE/RD      |
| 17    | — 0 — | LIGHT BLUE/BL      |
| 35    | — 0 — | LIGHT BLUE/GN      |
| 18    | — 0 — | GY/RD              |
| 36    | — 0 — | GY/GN              |
| SHELL | —     | BRAID + DRAIN WIRE |

| P/N        | x(m) | L(mm) | TOLERANCE(mm) |
|------------|------|-------|---------------|
| C36S-M0050 | 0.5  | 500   | +25/-0        |
| C36S-M0100 | 1    | 1000  | +25/-0        |
| C36S-M0150 | 1.5  | 1500  | +50/-0        |
| C36S-M0200 | 2    | 2000  | +50/-0        |
| C36S-M0300 | 3    | 3000  | +50/-0        |
| C36S-M0500 | 5    | 5000  | +50/-0        |

NOTE:

1. CABLE: UL2464 28AWG\*18P+AEB. PVC JACKET BEIGE(BG-02), OD:9.0±0.15MM.
2. CONNECTOR:P1: CENTRONICS 36PIN FEMALE: SOLDER ASSY NEW TYPE, GOLD FLASH CONTACTS. BLUE PBT INSULATION, W/METAL SHELL AND THIMBLE(OD:13MM).
- 3.PACKING: EACH CABLE IN A ZIP-LOCK POLY-BAG.  
LABEL (WHITE BACKGROUND WITH BLACK LETTERS) TO BE STAMPED ON POLYBAG.
- 4.100% ELECTRICAL TESTING.

|  |          |         |     |   |
|--|----------|---------|-----|---|
| NET MECHANISM Corp<br>www.cabling-ol.net |          |         |     |   |
| SCALE                                    | NONE     |         | REV | A |
| UNIT                                     | MM       |         |     |   |
| SHEET                                    | 1/1      | DWG NO. |     |   |
| DATE                                     | 11/13/04 |         |     |   |
| TITLE<br>CN36F TO OPEN                   |          |         |     |   |
| PART NO.<br>C36S-MXXXX                   |          |         |     |   |