



P1 CN36F

FEMALE BAIL LOCK HARDWARE(X2)

PIN OUT

P1	OPEN
1	BK
19	BK/WH
2	BR
20	BR/WH
3	RD
21	RD/WH
4	OR
22	OR/WH
5	YL
23	YL/BK
6	GN
24	GN/WH
7	BL
25	BL/WH
8	PP
26	PP/WH
9	GY
27	GY/BK

> 1 PAIR

P1	OPEN
10	WH
28	OR/BK
11	PK
29	RD/BK
12	LIGHT GREEN
30	GN/BK
13	PK/BK
31	PK/RD
14	PK/BL
32	PK/GN
15	LIGHT BLUE
33	LIGHT YELLOW
16	LIGHT BLUE/BK
34	LIGHT BLUE/RD
17	LIGHT BLUE/BL
35	LIGHT BLUE/GN
18	GY/RD
36	GY/GN

SHELL ——— BRAID + DRAIN WIRE

P/N	x(m)	L(mm)	TOLERANCE(mm)
C36S-M0050	0.5	500	+25/-0
C36S-M0100	1	1000	+25/-0
C36S-M0150	1.5	1500	+50/-0
C36S-M0200	2	2000	+50/-0
C36S-M0300	3	3000	+50/-0
C36S-M0500	5	5000	+50/-0

NOTE:

- CABLE: UL2464 28AWG*18P+AEB. PVC JACKET BEIGE(BG-02), OD:9.0±0.15MM.
- CONNECTOR:P1: CENTRONICS 36PIN FEMALE: SOLDER ASSY NEW TYPE, GOLD FLASH CONTACTS. BLUE PBT INSULATION, W/METAL SHELL AND THIMBLE(OD:13MM).
- PACKING: EACH CABLE IN A ZIP-LOCK POLY-BAG.
LABEL (WHITE BACKGROUND WITH BLACK LETTERS) TO BE STAMPED ON POLYBAG.
- 100% ELECTRICAL TESTING.

NET MECHANISM Corp www.cabling-ol.net				
SCALE	NONE		REV	A
UNIT	MM			
SHEET	1/1	DWG NO.		
DATE	11/13/04			
TITLE		CN36F TO OPEN		
PART NO.		C36S-MXXXX		