

P/N	X(M)	L(MM)	TOLERANCE(MM)
C50P-M0050	0.5	500	+25/-0
C50P-M0100	1	1000	+25/-0
C50P-M0150	1.5	1500	+50/-0
C50P-M0200	2	2000	+50/-0
C50P-M0300	3	3000	+50/-0
C50P-M0500	5	5000	+50/-0


NOTE:

1. CABLE: UL2464 28AWG*25P+AEB.PVC JACKET BEIGE(BG-02), OD:10.5±0.15MM.
2. CONNECTOR: P1:CENTRONICS 50PIN MALE: SOLDERASSY TRADITION TYPE,
GOLD FLASHCONTACTS.BLUE PBT INSULATION,W/METAL SHELL.
- 3.PACKING: EACH CABLE IN A ZIP-LOCK POLY-BAG.
LABEL (WHITE BACKGROUND WITH BLACK LETTERS) TO BE
STAMPED ON POLYBAG.
- 4.100% ELECTRICAL TESTING.

P1	OPEN
1	BK
26	BK/WH
2	BR
27	BR/WH
3	RD
28	RD/WH
4	OR
29	OR/WH
5	YL
30	YL/BK
6	GN
31	GN/WH
7	BL
32	BL/WH
8	PP
33	PP/WH
9	GY
34	GY/BK
10	WH (??)
35	OR/BK
11	PK
36	RD/BK
12	LIGHT GREEN
37	GN/BK
13	PK/BK
38	PK/RD
14	PK/BL
39	PK/GN

PIN OUT

P1	OPEN
15	LIGHT BLUE
40	LIGHT YELLOW
16	LIGHT BLUE/BK
41	LIGHT BLUE/RD
17	LIGHT BLUE/BL
42	LIGHT BLUE/GN
18	GY/RD
43	GY/GN
19	BL/BK
44	PP/BK
20	LIGHT GREEN/BK
45	LIGHT GREEN/RD
21	LIGHT GREEN/BL
46	LIGHT GREEN/GN
22	LIGHT YELLOW/BK
47	LIGHT YELLOW/RD
23	LIGHT YELLOW/BL
48	LIGHT YELLOW/GN
24	WHITE/BK
49	WHITE/RD
25	WHITE/BL
50	WHITE/GN
SHELL	BRAID + DRAIN WIRE



NET MECHANISM Corp www.cabling-ol.net				
SCALE	NONE		REV	A
UNIT	MM			
SHEET	1/1	DWG NO.		
DATE	11/13/04			
TITLE CN50M TO OPEN				
PART NO. C50P-MXXXX				