

P1 CN50M


P/N	X(M)	L(MM)	TOLERANCE(MM)
C50P-M0050	0.5	500	+25/-0
C50P-M0100	1	1000	+25/-0
C50P-M0150	1.5	1500	+50/-0
C50P-M0200	2	2000	+50/-0
C50P-M0300	3	3000	+50/-0
C50P-M0500	5	5000	+50/-0

NOTE:

1. CABLE: UL2464 28AWG*25P+AEB.PVC JACKET BEIGE(BG-02), OD:10.5±0.15MM.
2. CONNECTOR: P1:CENTRONICS 50PIN MALE: SOLDERASSY TRADITION TYPE, GOLD FLASHCONTACTS.BLUE PBT INSULATION,W/METAL SHELL.
- 3.PACKING: EACH CABLE IN A ZIP-LOCK POLY-BAG.
LABEL (WHITE BACKGROUND WITH BLACK LETTERS) TO BE STAMPED ON POLYBAG.
- 4.100% ELECTRICAL TESTING.

PIN OUT

P1	OPEN	P1	OPEN
1	BK	15	LIGHT BLUE
26	BK/WH	40	LIGHT YELLOW
2	BR	16	LIGHT BLUE/BK
27	BR/WH	41	LIGHT BLUE/RD
3	RD	17	LIGHT BLUE/BL
28	RD/WH	42	LIGHT BLUE/GN
4	OR	18	GY/RD
29	OR/WH	43	GY/GN
5	YL	19	BL/BK
30	YL/BK	44	PP/BK
6	GN	20	LIGHT GREEN/BK
31	GN/WH	45	LIGHT GREEN/RD
7	BL	21	LIGHT GREEN/BL
32	BL/WH	46	LIGHT GREEN/GN
8	PP	22	LIGHT YELLOW/BK
33	PP/WH	47	LIGHT YELLOW/RD
9	GY	23	LIGHT YELLOW/BL
34	GY/BK	48	LIGHT YELLOW/GN
10	WH (??)	24	WHITE/BK
35	OR/BK	49	WHITE/RD
11	PK	25	WHITE/BL
36	RD/BK	50	WHITE/GN
12	LIGHT GREEN	SHELL	BRAID + DRAIN WIRE
37	GN/BK		
13	PK/BK		
38	PK/RD		
14	PK/BL		
39	PK/GN		



NET MECHANISM Corp				
www.cabling-ol.net				
SCALE	NONE		REV	A
UNIT	MM			
SHEET	1/1	DWG NO.		
DATE	11/13/04			
TITLE				
CN50M TO OPEN				
PART NO.				
C50P-MXXXX				