

P1 CN50M


P2 CN50M

PIN OUT

P1	P2
1	1 BK
26	26 BK/WH
2	2 BR
27	27 BR/WH
3	3 RD
28	28 RD/WH
4	4 OR
29	29 OR/WH
5	5 YL
30	30 YL/BK
6	6 GN
31	31 GN/WH
7	7 BL
32	32 BL/WH
8	8 PP
33	33 PP/WH
9	9 GY
34	34 GY/BK
10	10 WH
35	35 OR/BK
11	11 PK
36	36 RD/BK
12	12 LIGHT GREEN
37	37 GN/BK
13	13 PK/BK
38	38 PK/RD
14	14 PK/BL
39	39 PK/GN

P1	P2
15	15 LIGHT BLUE
40	40 LIGHT YELLOW
16	16 LIGHT BLUE/BK
41	41 LIGHT BLUE/RD
17	17 LIGHT BLUE/BL
42	42 LIGHT BLUE/GN
18	18 GY/RD
43	43 GY/GN
19	19 BL/BK
44	44 PP/BK
20	20 LIGHT GREEN/BK
45	45 LIGHT GREEN/RD
21	21 LIGHT GREEN/BL
46	46 LIGHT GREEN/GN
22	22 LIGHT YELLOW/BK
47	47 LIGHT YELLOW/RD
23	23 LIGHT YELLOW/BL
48	48 LIGHT YELLOW/GN
24	24 WHITE/BK
49	49 WHITE/RD
25	25 WHITE/BL
50	50 WHITE/GN

SHELL ——— SHELL(BRAID + DRAIN WIRE)



P/N	X(M)	L(MM)	TOLERANCE(MM)
C50PP-M0050	0.5	500	+50/-0
C50PP-M0100	1	1000	+75/-0
C50PP-M0150	1.5	1500	+75/-0
C50PP-M0200	2	2000	+75/-0
C50PP-M0300	3	3000	+75/-0
C50PP-M0500	5	5000	+150/-0

NOTE:

1. CABLE: UL2464 28AWG\*25P+AEB.PVC JACKET BEIGE(BG02), OD:10.5±0.15mm.
2. CONNECTOR: P1 AND P2:CENTRONICS 50PIN MALE: SOLDERASSY TRADITION TYPE, GOLD FLASHCONTACTS.BLUE PBT INSULATION,W/METAL SHELL AND THIMBLE(OD:13MM).
- 3.PACKING: EACH CABLE IN A ZIP-LOCK POLY-BAG.LABEL (WHITE BACKGROUND WITH BLACK LETTERS) TO BE STAMPED ON POLYBAG.
- 4.100% ELECTRICAL TESTING.

MERCHANDISE MOQ	EACH 50PCS			
LEAD TIME	14 DAY			
CABLE MOQ	EACH 3000M			
CONNECTOR MOQ	EACH 1000PCS			
NET MECHANISM Corp www.cabling-ol.net				
SCALE	NONE		REV	B
UNIT	MM		DWG NO.	
SHEET	1/1			
DATE	10/26/13			
TITLE	CN50M TO CN50M			
PART NO.	C50PP-MXXXX			