


PIN OUT

| P1 | P2 |
|----|-------------|
| 1 | BK |
| 26 | BK/WH |
| 2 | BR |
| 27 | BR/WH |
| 3 | RD |
| 28 | RD/WH |
| 4 | OR |
| 29 | OR/WH |
| 5 | YL |
| 30 | YL/BK |
| 6 | GN |
| 31 | GN/WH |
| 7 | BL |
| 32 | BL/WH |
| 8 | PP |
| 33 | PP/WH |
| 9 | GY |
| 34 | GY/BK |
| 10 | WH |
| 35 | OR/BK |
| 11 | PK |
| 36 | RD/BK |
| 12 | LIGHT GREEN |
| 37 | GN/BK |
| 13 | PK/BK |
| 38 | PK/RD |
| 14 | PK/BL |
| 39 | PK/GN |

| P1 | P2 |
|----|-----------------|
| 15 | LIGHT BLUE |
| 40 | LIGHT YELLOW |
| 16 | LIGHT BLUE/BK |
| 41 | LIGHT BLUE/RD |
| 17 | LIGHT BLUE/BL |
| 42 | LIGHT BLUE/GN |
| 18 | GY/RD |
| 43 | GY/GN |
| 19 | BL/BK |
| 44 | PP/BK |
| 20 | LIGHT GREEN/BK |
| 45 | LIGHT GREEN/RD |
| 21 | LIGHT GREEN/BL |
| 46 | LIGHT GREEN/GN |
| 22 | LIGHT YELLOW/BK |
| 47 | LIGHT YELLOW/RD |
| 23 | LIGHT YELLOW/BL |
| 48 | LIGHT YELLOW/GN |
| 24 | WHITE/BK |
| 49 | WHITE/RD |
| 25 | WHITE/BL |
| 50 | WHITE/GN |

SHELL ——— SHELL(BRAID + DRAIN WIRE)



FEMALE BAIL LOCK HARDWARE(X2)

| P/N | X(M) | L(MM) | TOLERANCE(MM) |
|-------------|------|-------|---------------|
| C50PS-M0050 | 0.5 | 500 | +25/-0 |
| C50PS-M0100 | 1 | 1000 | +25/-0 |
| C50PS-M0150 | 1.5 | 1500 | +50/-0 |
| C50PS-M0200 | 2 | 2000 | +50/-0 |
| C50PS-M0300 | 3 | 3000 | +50/-0 |
| C50PS-M0500 | 5 | 5000 | +50/-0 |

NOTE:

- CABLE: UL2464 28AWG*25P+AEB. PVC JACKET BEIGE(BG-02),OD:10.5±0.15MM.
- CONNECTOR: P1:CENTRONICS 50PIN MALE: SOLDER ASSY TRADITION TYPE, GOLD FLASH CONTACTS. BLUE PBT INSULATION,W/METAL SHELL AND THIMBLE(OD:13MM). P2:CENTRONICS 50PIN FEMALE: SOLDER ASSY NEW TYPE, GOLD FLASHCONTACTS. BLUE PBT INSULATION, W/METAL SHELL AND THIMBLE(OD:13MM).
- PACKING: EACH CABLE IN A ZIP-LOCK POLY-BAG.LABEL (WHITE BACKGROUND WITH BLACK LETTERS) TO BE STAMPED ON POLYBAG.
- 100% ELECTRICAL TESTING.

NET MECHANISM Corp
www.cabling-ol.net

| | | | | |
|-------|----------|---------|-----|---|
| SCALE | NONE | | REV | A |
| UNIT | MM | | | |
| SHEET | 1/1 | DWG NO. | | |
| DATE | 11/13/04 | | | |

TITLE
CN50M TO CN50F

PART NO.
C50PS-MXXXX