



PIN OUT

P1 CN50M

P1	P2
1	BK
26	BK/WH
2	BR
27	BR/WH
3	RD
28	RD/WH
4	OR
29	OR/WH
5	YL
30	YL/BK
6	GN
31	GN/WH
7	BL
32	BL/WH
8	PP
33	PP/WH
9	GY
34	GY/BK
10	WH
35	OR/BK
11	PK
36	RD/BK
12	LIGHT GREEN
37	GN/BK
13	PK/BK
38	PK/RD
14	PK/BL
39	PK/GN

P1	P2
15	LIGHT BLUE
40	LIGHT YELLOW
16	LIGHT BLUE/BK
41	LIGHT BLUE/RD
17	LIGHT BLUE/BL
42	LIGHT BLUE/GN
18	GY/RD
43	GY/GN
19	BL/BK
44	PP/BK
20	LIGHT GREEN/BK
45	LIGHT GREEN/RD
21	LIGHT GREEN/BL
46	LIGHT GREEN/GN
22	LIGHT YELLOW/BK
47	LIGHT YELLOW/RD
23	LIGHT YELLOW/BL
48	LIGHT YELLOW/GN
24	WHITE/BK
49	WHITE/RD
25	WHITE/BL
50	WHITE/GN

SHELL ——— SHELL(BRAID + DRAIN WIRE)

> 1 PAIR

P2 CN50F
FEMALE BAIL LOCK HARDWARE(X2)

P/N	X(M)	L(MM)	TOLERANCE(MM)
C50PS-M0050	0.5	500	+25/-0
C50PS-M0100	1	1000	+25/-0
C50PS-M0150	1.5	1500	+50/-0
C50PS-M0200	2	2000	+50/-0
C50PS-M0300	3	3000	+50/-0
C50PS-M0500	5	5000	+50/-0

NOTE:

- CABLE: UL2464 28AWG*25P+AEB. PVC JACKET BEIGE(BG-02),OD:10.5±0.15MM.
- CONNECTOR: P1:CENTRONICS 50PIN MALE: SOLDER ASSY TRADITION TYPE, GOLD FLASH CONTACTS. BLUE PBT INSULATION,W/METAL SHELL AND THIMBLE(OD:13MM). P2:CENTRONICS 50PIN FEMALE: SOLDER ASSY NEW TYPE, GOLD FLASHCONTACTS. BLUE PBT INSULATION, W/METAL SHELL AND THIMBLE(OD:13MM).
- PACKING: EACH CABLE IN A ZIP-LOCK POLY-BAG.LABEL (WHITE BACKGROUND WITH BLACK LETTERS) TO BE STAMPED ON POLYBAG.
- 100% ELECTRICAL TESTING.

NET MECHANISM Corp
www.cabling-ol.net

SCALE	NONE		REV	A
UNIT	MM			
SHEET	1/1	DWG NO.		
DATE	11/13/04			

TITLE	CN50M TO CN50F
PART NO.	C50PS-MXXXX