


P/N	X(M)	L(MM)	TOLERANCE(MM)
C50S-M0050	0.5	500	+25/-0
C50S-M0100	1	1000	+25/-0
C50S-M0150	1.5	1500	+50/-0
C50S-M0200	2	2000	+50/-0
C50S-M0300	3	3000	+50/-0
C50S-M0500	5	5000	+50/-0

NOTE:

1. CABLE: UL2464 28AWG\*25P+AEB.PVC JACKET BEIGE(BG-02), OD:10.5±0.15MM.
2. CONNECTOR:P1: CENTRONICS 50PIN FEMALE: SOLDER ASSY NEW TYPE, GOLD FLASHCONTACTS. BLUE PBT INSULATION, W/METAL SHELL AND THIMBLE(OD:13MM).
- 3.PACKING: EACH CABLE IN A ZIP-LOCK POLY-BAG.LABEL (WHITE BACKGROUND WITH BLACK LETTERS) TO BE STAMPED ON POLYBAG.
- 4.100% ELECTRICAL TESTING.

PIN OUT	
P1	OPEN
1	BK
26	BK/WH
2	BR
27	BR/WH
3	RD
28	RD/WH
4	OR
29	OR/WH
5	YL
30	YL/BK
6	GN
31	GN/WH
7	BL
32	BL/WH
8	PP
33	PP/WH
9	GY
34	GY/BK
10	WH
35	OR/BK
11	PK
36	RD/BK
12	LIGHT GREEN
37	GN/BK
13	PK/BK
38	PK/RD
14	PK/BL
39	PK/GN

PIN OUT	
P1	OPEN
15	LIGHT BLUE
40	LIGHT YELLOW
16	LIGHT BLUE/BK
41	LIGHT BLUE/RD
17	LIGHT BLUE/BL
42	LIGHT BLUE/GN
18	GY/RD
43	GY/GN
19	BL/BK
44	PP/BK
20	LIGHT GREEN/BK
45	LIGHT GREEN/RD
21	LIGHT GREEN/BL
46	LIGHT GREEN/GN
22	LIGHT YELLOW/BK
47	LIGHT YELLOW/RD
23	LIGHT YELLOW/BL
48	LIGHT YELLOW/GN
24	WHITE/BK
49	WHITE/RD
25	WHITE/BL
50	WHITE/GN
SHELL	BRAID + DRAIN WIRE



NET MECHANISM Corp www.cabling-ol.net				
<b>SCALE</b>	<b>NONE</b>		<b>REV</b>	<b>A</b>
<b>UNIT</b>	<b>MM</b>			
<b>SHEET</b>	<b>1/1</b>	<b>DWG NO.</b>		
<b>DATE</b>	11/13/04			
<b>TITLE</b>				
CN50F TO OPEN				
<b>PART NO.</b>				
C50S-MXXXX				