



CHART:

P/N	X(M)	L(MM)	TOLERANCE(MM)
C50SS-F0025	0.25	250	+15/-0
C50SS-F0050	0.5	500	+50/-0
C50SS-F0075	0.75	750	+50/-0
C50SS-F0100	1	1000	+75/-0
C50SS-F0150	1.5	1500	+75/-0
C50SS-F0200	2	2000	+75/-0
C50SS-F0300	3	3000	+75/-0

PIN OUT

P1	RD	P2
1	—	1
2	—	2
3	—	3
4	—	4
5	—	5
•	—	•
•	—	•
•	—	•
50	—	50

Note:  
 1. CABLE: UL2651 28AWG\*50C P=1.27 MM, GRAY PVC FLAT CABLE.  
 2. P1&P2: CN 50F, IDC TYPE, BLUE INSULATION WITH THREE PARTS.  
 3. THE CABLE SHALL BE 100% ELECTRICAL TEST.

NET MECHANISM Corp			
www.cabling-ol.net			
SCALE	NONE	⊕	REV
UNIT	MM		
SHEET	1/1	DWG NO.	
DATE	11/13/04	TITLE	
CN50F IDC TO CN50F IDC TYPE			
PART NO.			
C50SS-FXXXX			