



L(MM)	TOLERANCE(MM)
100~499	+25/-0
500~999	+50/-0
1000~4999	+75/-0
5000~14999	+150/-0
15000~49999	+300/-0

PIN OUT:

P1	PAIRS	P2	WIRE COLOR
1	—○—	3	WHITE/ORANGE
2	—○—	6	ORANGE
3	—○—	1	WHITE/GREEN
6	—○—	2	GREEN
5	—○—	8	WHITE/BLUE
4	—○—	7	BLUE
7	—○—	4	WHITE/BROWN
8	—○—	5	BROWN

C5E-CRYYXXX  
 ——— LENGTH UNIT FT  
 ——— COLOR.

- NOTE:
- 1.CABLE:UTP CAT.5e CABLE.4P\*24AWG(7/0.205)(BARE COPPER.INSULATION:HD-PE.OD:0.98±0.05mm)+OUTER JACKET:PVC,OD:5.6±0.2mm.
  - 2.CONN.:P1 & P2 8P8C PLUG, LONG BODY, DOUBLE LAY, GOLD PLATED 50U"
  - 3.ALL BOOT:MOLDING 60P PVC.
  - 4.CABLE ASS'Y MUST PASS CONTINUITY TEST.
  - 5.MOLD NO:BOOT-03

MERCHANDISE MOQ	EACH 1PCS		
LEAD TIME	12 DAY		
CABLE MOQ			
CONNECTOR MOQ			
NET MECHANISM Corp www.cabling-ol.net			
SCALE	NONE		REV C
UNIT	MM		
SHEET	1/1	DWG NO.	
DATE	11/18/13		
TITLE	8P8C PLUG/8P8C PLUG		
PART NO.	C5E-CRYYXXX		

REV	DESCRIPTION OF CHANGE	DATE
C	CHANGING DIMENSION TOLERANCE	11/18/13
B	CHANGE MOLD TYPE FOR ASS'Y BOOT	04/29/10
A	INITIAL RELEASE	03/16/06