



L(MM)	TOLERANCE(MM)
100~499	+15/-0
500~999	+50/-0
1000~4999	+75/-0
5000~14999	+150/-0
15000~49999	+300/-0

C5E-CRYYXXX  
 └───┬─── LENGTH UNIT FT  
 └───┴─── COLOR.

PIN OUT:

P1	PAIRS	P2	WIRE COLOR
1	—○—	3	WHITE/ORANGE
2	—○—	6	ORANGE
3	—○—	1	WHITE/GREEN
6	—○—	2	GREEN
5	—○—	8	WHITE/BLUE
4	—○—	7	BLUE
7	—○—	4	WHITE/BROWN
8	—○—	5	BROWN

NOTE:

- 1.CABLE:UTP CAT.5e CABLE.4P\*24AWG(7/0.205)(BARE COPPER.INSULATION:HD-PE.OD:0.98±0.05mm)+OUTER JACKET:PVC,OD:5.6±0.2mm.
- 2.CONN.:P1,P2 8P8C MODULAR,SHORT BODY, DOUBLE LAY,GOLD PLATED 50u”.
- 3.ALL HOOD:MOLDING 60P PVC.
- 4.CABLE ASS'Y MUST PASS CONTINUITY TEST.

NET MECHANISM Corp www.cabling-ol.net			
SCALE	NONE		REV B
UNIT	MM		
SHEET	1/1	DWG NO.	
DATE	03/16/06		
TITLE 8P8C PLUG/8P8C PLUG			
PART NO. C5E-CRYYXXX			