


L(MM)	TOLERANCE(MM)
100~499	+15/-0
500~999	+50/-0
1000~4999	+75/-0
5000~14999	+150/-0
15000~49999	+300/-0



PIN OUT:

P1	PAIRS	P2	WIRE COLOR
1	—○—	3	WHITE/ORANGE
2	—○—	6	ORANGE
3	—○—	1	WHITE/GREEN
6	—○—	2	GREEN
5	—○—	8	WHITE/BLUE
4	—○—	7	BLUE
7	—○—	4	WHITE/BROWN
8	—○—	5	BROWN

C5E-CRYYXXX
 LENGTH UNIT FT
 COLOR.

NOTE:

- 1.CABLE:UTP CAT.5e CABLE.4P*24AWG(7/0.205)(BARE COPPER.INSULATION:HD-PE.OD:0.98±0.05mm)+OUTER JACKET:PVC,OD:5.6±0.2mm.
- 2.CONN.:P1 & P2 8P8C PLUG, LONG BODY, DOUBLE LAY, GOLD PLATED 50U"
- 3.ALL BOOT:MOLDING 60P PVC.
- 4.CABLE ASS'Y MUST PASS CONTINUITY TEST.
- 5.MOLD NO:BOOT-03

MERCHANDISE MOQ	EACH 1PCS
LEAD TIME	12 DAY
CABLE MOQ	
CONNECTOR MOQ	

NET MECHANISM Corp
 www.cabling-ol.net

SCALE	NONE		REV	B
UNIT	MM			
SHEET	1/1	DWG NO.		
DATE	04/29/10			

TITLE 8P8C PLUG/8P8C PLUG

B	CHANGE MOLD TYPE FOR ASS'Y BOOT	04/29/10
A	INITIAL RELEASE	03/16/06
REV	DESCRIPTION OF CHANGE	DATE

PART NO. C5E-CRYYXXX