


P/N	X(M)	L(MM)	TOLERANCE(MM)
C5E-R3-BL005	0.5	500	+50/-0
C5E-R3-BL010	1	1000	+75/-0
C5E-R3-BL020	2	2000	+75/-0
C5E-R3-BL030	3	3000	+75/-0
C5E-R3-BL050	5	5000	+150/-0
C5E-R3-BL075	7.5	7500	+150/-0
C5E-R3-BL100	10	10000	+150/-0
C5E-R3-BL150	15	15000	+300/-0

PIN OUT:

P1	PAIRS	P2	WIRE COLOR
1	—○—	1	WHITE/ORANGE
2	—○—	2	ORANGE
3	—○—	3	WHITE/GREEN
6	—○—	6	GREEN
5	—○—	5	WHITE/BLUE
4	—○—	4	BLUE
7	—○—	7	WHITE/BROWN
8	—○—	8	BROWN

NOTE:

- 1.CABLE:UTP CAT.5E CABLE.4P*28AWG(7/0.12)(BARE COPPER.INSULATION:HD-PE.OD:0.6±0.03mm)+OUTER JACKET:PVC,OD:3.5±0.15mm.
- 2.CONN.:P1,P2 8P8C MODULAR,SHORT BODY, SINGLE LAY,GOLD PLATED 50u".
- 3.ALL HOOD:MOLDING 60P PVC.
- 4.CABLE ASS'Y MUST PASS CONTINUITY TEST.

NET MECHANISM Corp www.cabling-ol.net				
SCALE	NONE		REV	A
UNIT	MM			
SHEET	1/1	DWG NO.		
DATE	10/07/05			
TITLE 8P8C PLUG/8P8C PLUG				
PART NO. C5E-R3-YYXXX				