



L(MM)	TOLERANCE(MM)
100~499	+15/-0
500~999	+50/-0
1000~4999	+75/-0
5000~14999	+150/-0
15000~49999	+300/-0

PIN OUT:

P1	PAIRS	P2	WIRE COLOR
1	—○—	1	WHITE/ORANGE
2	—○—	2	ORANGE
3	—○—	3	WHITE/GREEN
6	—○—	6	GREEN
5	—○—	5	WHITE/BLUE
4	—○—	4	BLUE
7	—○—	7	WHITE/BROWN
8	—○—	8	BROWN
SHELL	————	SHELL	DRAIN

C5ES-YYXXX
 ———— LENGTH UNIT: FT
 ———— COLOR: BK, RD, YL, GN, BL, GY, WH.

- NOTE:
- 1.CABLE:FTP CAT.5E CABLE.4P*24AWG(7/0.203)(BARE COPPER.INSULATION:HD-PE.OD:0.95±0.05mm)+MYLAR+DRAIN+AL/MY+OUTER JACKET:PVC. OD:5.9±0.15mm.
 - 2.CONN.:P1,P2 8P8C PLUG,ALL SHELL,LONG BODY,DOUBLE LAY. GOLD PLATED 50u".
 - 3.ALL HOOD:MOLDING 60P PVC.
 - 4.CABLE ASS'Y MUST PASS CONTINUITY TEST.

NET MECHANISM Corp www.cabling-ol.net				
SCALE	NONE		REV	A
UNIT	MM			
SHEET	1/1	DWG NO.		
DATE	03/16/06			
TITLE 8P8C PLUG TO 8P8C PLUG				
PART NO. C5ES-YYXXX				