



L(MM)	TOLERANCE(MM)
100~499	+15/-0
500~999	+50/-0
1000~4999	+75/-0
5000~14999	+150/-0
15000~49999	+300/-0

PIN OUT:

P1	PAIRS	P2	WIRE COLOR
1	—○—	1	WHITE/ORANGE
2	—○—	2	ORANGE
3	—○—	3	WHITE/GREEN
6	—○—	6	GREEN
5	—○—	5	WHITE/BLUE
4	—○—	4	BLUE
7	—○—	7	WHITE/BROWN
8	—○—	8	BROWN
SHELL	—	SHELL	DRAIN

C5ES-YYXXX  
 ———— LENGTH UNIT:FT  
 ———— COLOR:BK,RD,YL,GN,BL,GY,WH.

- NOTE:
- CABLE:FTP CAT.5E CABLE.4P\*24AWG(7/0.203)(BARE COPPER.INSULATION:HD-PE.OD:0.95±0.05mm)+MYLAR+DRAIN+AL/MY+OUTER JACKET:PVC. OD:5.9±0.15mm.
  - CONN.:P1,P2 8P8C PLUG,ALL SHELL,LONG BODY,DOUBLE LAY. GOLD PLATED 50u".
  - ALL BOOT:MOLDING 60P PVC.
  - CABLE ASS'Y MUST PASS CONTINUITY TEST.
  - MOLD NO:BOOT-03

B	CHANGE MOLD TYPE FOR ASS'Y BOOT	04/29/10
A	INITIAL RELEASE	03/16/06
REV	DESCRIPTION OF CHANGE	DATE

MERCHANDISE MOQ	EACH 1PCS		
LEAD TIME	12 DAY		
CABLE MOQ			
CONNECTOR MOQ			
NET MECHANISM Corp www.cabling-ol.net			
SCALE	NONE		REV B
UNIT	MM		
SHEET	1/1	DWG NO.	
DATE	04/29/10		
TITLE	8P8C PLUG TO 8P8C PLUG		
PART NO.	C5ES-YYXXX		